
The Soraa Optima Series electronic transformer is ideal for 12V LED or halogen lamps. It's highly efficient, works with trailing edge dimmers, is easy to install, and features open circuit, short circuit, overload, and overtemperature protections and a 30,000 hour lifetime.





Construction

Thermally stable shatter proof PC plastic casing. Primary Terminal 2-pole, Screw 5.2mm Secondary Terminal 2-pole, Screw 3.2mm

Dimming

Compatible with trailing edge dimmers. Visit www.soraa.com for details

Compliance

Safety RFI Harmonics Immunity

EN 61347-2-1 EN 55015 EN61000-3-2 EN 61547

Lifetime & Warranty

Average service life: 30,000 hours. Three year warranty. See www.soraa.com.

Ambient

Storage Temperature- ts-20 to +70°COperating Temperature- ta-20 to +50°CCase Temperature @ tc+80°C

Protection

No Load, Overload, Short Circuit, Overtemperature

Withstand Voltage

3.75KVAC, leakage < 5.0mA, 60S

Auto-Recovery if


Fault is Removed

Electrical: Input

Rated Input Voltage	220-240VAC
Input Current (Full Load)	0.29A
Input Frequency	50/60Hz
Max Input Power	71W
Power Factor	≥ 0.99
THD (Full Load)	≤ 10%
Efficiency (Full Load)	≥ 93%
Input Capacitance	100nF

Electrical: Output

Output Voltage11.2V ±5%Output Current6.0AOutput Power (Full Load)67.2WOperating Frequency32-38KHz





Order Number Sample Number: TCVW - P - 12-600 - 70 - 01 - S3

Constant	Туре	Input Voltage	Dimming	Output Voltage	Output Current	Power	Variation	Region
т	CV Constant Voltage	W 230VAC	P Phase Dim	12 12VAC	600 6.0A (Full Load)	70 Max Input (W)	01 Default	S3 International